



PELI STORM CASE ENGINEERING TEST STANDARDS COMPLIANCE 10/17/2011

All Peli Storm Case containers meet the applicable requirements of MIL---STD---810F, FED---STD---101C and ATA---300 (Category 1) as follows:

- ATA---300 IMPACT RESISTANCE TEST, Category 1
- ATA---300 VIBRATION, Sweep and Dwell
- FED---STD---101C VIBRATION, Method 5019 Loose Cargo Bounce
- FED---STD---101C ROOM TEMPERATURE (+70°F) DROP TESTING, Method 5007.1, Paragraph 6.3, Procedure A, Level A
- FED---STD---101C LOW TEMPERATURE (---20°F) DROP TESTING, Method 5007.1, Paragraph 6.3, Procedure A, Level A
- FED---STD---101C HIGH TEMPERATURE (+140°F) DROP TESTING, Method 5007.1, Paragraph 6.3, Procedure A, Level A
- FED---STD---101C FALLING RAIN, Method 5009.1, Section 6.7.1
- MIL---STD---810F FALLING RAIN, Method 506.4, Procedure II of 4.1.2
- ATA---300 / ASTM D591---99 FALLING RAIN
- MIL---STD---810F IMMERSION, Method 512.4
- FED---STD---101C IMMERSION

Principal Research Engineer
Research and Product Development
P.O. Box 201
147 North Main Street, South Deerfield, MA 01373
www.peli.com

Peli Products

Peli Cases | Peli Storm Cases | Peli-Hardigg Cases | Peli Advanced Lighting Systems